

**Cooler Area:** 

# HOS BROWNING

## **HOSMAX300 Offshore Supply Vessel**



### **DIMENSIONS AND REGULATORY INFORMATION**

292 ft 0 in (89.0 m) 64 ft 0 in (19.5 m) 20 ft 0 in (6.10 m) **Draft Max:** Beam: Length: 3.764 GT 1,266 NT 11 ft 3 in (3.43 m) **Gross:** Net: **Draft Min:** 

9587398 31015887326 O.N.: IMO: Flag: Mexico

**Certifications:** Oceans-SOLAS

Classifications: Loadline, American Bureau of Shipping, +DPS-2, FFV-1, (E), +A1, +ACC, +AMS, OSV, UWILD, OSR-C2

#### **PERFORMANCE**

**Cruise Speed:** 10.0 kts 140 gal/hr (530 l/hr) Max Speed: 12.0 kts 205 gal/hr (776 l/hr)

### PROPULSION, MACHINERY AND STEERING

7,300 kW 4 x Cummins QSK60DM **Total Rating: Main Engines: Main Propulsion:** 2 x Schottel Azimuthing Z-Drives 6,700 hp **Total Rating: Bow Thruster:** 2 x Schottel FPP Tunnel **Total Rating:** 3,160 hp

> 690V/60/3 phase **Power Generation:**

## **CAPACITIES AND DELIVERY RATES**

196 ft x 56 ft (10,930 ft<sup>2</sup>) 5,553 LT (5,642 MT) Deck Area: **Deadweight:** 

59.7 m x 17.1 m (1,015.4 m<sup>2</sup>)

4,200 LT (4,267 MT) 1,024 lbs/ft<sup>2</sup> (5 MT/m<sup>2</sup>) **Deck Cargo: Deck Load Rating:** 

80 psi (5.5 bar) **System Pressure:** 

**Dry Bulk:** 14,347 ft<sup>3</sup> (406 m<sup>3</sup>) 19,516 bbl (3,102 m<sup>3</sup>) **Liquid Mud:** 1,713 bbl (272 m<sup>3</sup>) Methanol: 17,190 gal (65 m<sup>3</sup>) **Potable Water:** 254,841 gal (965 m<sup>3</sup>) **Rig Fuel:** Rig Water: 547,580 gal (2,073 m<sup>3</sup>)

1,000 GPM (227 m<sup>3</sup>/hr) **Discharge Rate: Discharge Rate:** 500 GPM (114 m<sup>3</sup>/hr) 2,000 USG/day (7.6 m<sup>3</sup>/day) Watermaker Cap.: 750 GPM (170 m<sup>3</sup>/hr) **Discharge Rate: Discharge Rate:** 750 GPM (170 m<sup>3</sup>/hr)

500 ft<sup>3</sup> (14 m<sup>3</sup>) 375 ft<sup>3</sup> (11 m<sup>3</sup>) Freezer Area:

## **ELECTRONICS**

AIS, Anemometer, Auto Pilot, CCTV Cameras, Cyscan, Depth Sounder, DGPS w/ AIS, DSDL, EPIRB, GMDSS "A3", Gyro Compass, Joystick Control, Mag Compass, MAMS/VMS, Navtex, Public Phone System w/ loudhailer, Radascan, S-band Radar, SARTs, Speed Log, SSAS, VHF Radio, VHF Radio (Handheld), VSAT, X-band Radar, VERIPOS

#### **ACCOMMODATIONS**

14 air conditioned/heated staterooms certified for 31 person berthing.

#### SPECIAL FEATURES

Oil Spill Recovery: **Recovered Oil Capacity:** 19,516 bbl (3,102 m<sup>3</sup>) (>60 °C FP) ABS Capability Class 2

Number of Fire Monitors: 2 Off-ship Firefighting: ABS FiFi 1

10,568 gal/min (2,402 m<sup>3</sup>/hr) **Total Flow Rate:** 

**Deck Crane:** 1 x North Pacific MCT-327 Max Lift @ Max Radius: 0.68 MT @ 27 ft

Max Lift @ Min Radius: 1.59 MT @ 5 ft

**Cargo Tank Cleaning:** 2x dual nozzle, dual rotation w/ 110 GPM (25 m<sup>3</sup>/hr)

@ 145 psi (10 bar) total each tank

NOTICE: The information contained herein is provided solely for the convenience of reference, and Hornbeck does not warrant the accuracy or completeness of the data, which may vary from the current condition of the vessel or equipment. Hornbeck accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.

Phone: (985)727-2000 (985)727-3606 Date: 05/13/2021